

MARLINE

Product Specification Marline Premium 2 Temps

Valid from: 2022-03-12

Parameter	Unit	Requirement	Method
Appearance	-	Clear & Bright	Visual Inspection
RON	-	≥ 93.0	EN ISO 5164
MON	-	≥ 90.0	EN ISO 5163
Density at 15 °C	kg/m ³	680 – 720	EN ISO 12185
DVPE at 37.8 °C	kPa	55.0 – 65.0	EN 13016-1
Olefin content	% vol	< 1.0	EN 15553
Aromatic content	% vol	< 1.0	SS 155120 Eq. to ASTM D 5443
Benzene content	% vol	< 0.08	EN 238
Cyclohexane (up to C8)	% vol	< 2.0	ASTM D 5134
Normalhexane	% vol	< 0.5	ASTM D 5134
Manganese	mg/L	≤ 2.0	EN 16136
Sulphur	mg/kg	≤ 10.0	EN ISO 20846
Lead	mg/L	≤ 2.0	EN 237
Evaporated at 70 °C	% vol	15.0 - 42.0	EN ISO 3405
Evaporated at 150 °C	% vol	≥ 75.0	EN ISO 3405
Temperature at 50 % evaporated	°C	90 – 105	EN ISO 3405
FBP	°C	≤ 200	EN ISO 3405
Distillation residue	% vol	< 3.0	EN ISO 3405
Oil content	% vol	1.5 - 2.0	
Copper corrosion 3h at 50 °C	Acc. to scale	Class 1	EN ISO 2160

Marline

ZA Sud Essor

5, rue Marcel Laloyeau

91150 Brières Les Scellés

Tel +33(0)1 69 92 90 99

Fax +33(0)1 60 80 15 58

Mail: info@marline.fr